Author Index

Abdel-Malek, K.	Bone registration method for robot assisted surgery: pedicle screw insertion	221–233
Addlesee, A. J.	A prototype model for renal vasculature and its application in haemodialyser miniaturization	479–482
Akkaş, N.	Biomechanics of the Gazi type pelvis external skeletal fixator	401–409
AL-Saffar, A.	Biological reaction to debris in relation to joint prostheses	187–197
Anissian, L.	Charnley wear model for validation of hip simulators—ball diameter versus polytetrafluoroethylene and polyethylene wear	25–36
Arambula-Cosio, F.	The Probot—an active robot for prostate resection	317–325
Ash, H. E.	Further studies into proximal interphalangeal joint dimensions for the design of a surface replacement prosthesis: medullary cavities and transverse plane shapes	377–390
Ateshian, G. A.	Rolling resistance of articular cartilage due to interstitial fluid flow	419–424
Barker, T. M.	Calculation of multi-segment rigid body dynamics using MATLAB	483–487
Bigsby R. J. A.	Wear of ultra-high molecular weight polyethylene acetabular cups in a physiological hip joint simulator in the anatomical position using bovine serum as a lubricant	265–269
Bobyn, J. D.	Kinematics of the MATCO® hip simulator and issues related to wear testing of metal–metal implants	89–99
Bonfield, W.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Bowker, P.	Quantitative assessment of anterior cruciate ligament deficiency: applied load versus applied displacement	441–449
Brett, P. N.	A technique for measuring contact force distribution in minimally invasive surgical procedures	309–316
Brett, P. N.	Simulation of resistance forces acting on surgical needles	335–347
Buckley, M. A.	Computer simulation of the dynamics of a human arm and orthosis linkage mechanism	349–357
Burgess, I. C.	Development of a six station knee wear simulator and preliminary wear results	37–47
Cain, T. J.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Campbell, P.	Application of numerical descriptors to the characterization of wear particles obtained from joint replacements	1–10
Carr, A.	Simulation of resistance forces acting on surgical needles	335–347
Chan, F. W.	Kinematics of the MATCO® hip simulator and issues related to wear testing of metal–metal implants	89–99
Çitipitioğlu, E.	Biomechanics of the Gazi type pelvis external skeletal fixator	401–409
Clarke, I. C.	Charnley wear model for validation of hip simulators—ball diameter versus polytetrafluoroethylene and polyethylene wear	25–36
Clift, S. E.	The influence of the stem–cement interface in total hip replacement—a comparison of experimental and finite element approaches	181–186
Cobb, J. C.	Active compliance in robotic surgery—the use of force control as a dynamic constraint	285–292
Cunningham, J. L.	Development of a six station knee wear simulator and preliminary wear results	37–47
Cunningham, J. L.	Factors contributing to the wear of polyethylene in clinical practice	49–57
Cunningham, J. L.	The pathogenesis of osteolysis in two different cementless hip replacements	59–63
Cuschieri, A.	Technological aspects of minimal access surgery	129–144
Davies, B. L.	Active compliance in robotic surgery—the use of force control as a dynamic constraint	285–292
Davies, B. L.	The Probot—an active robot for prostate resection	317–325
Dolan, M. J.	Quality framework for force plate testing	213–219
Dowson, D.	The wear of ultra-high molecular weight polyethylene sliding on metallic and ceramic counterfaces representative of current femoral surfaces in joint replacement	17–24
Dowson, D.	Analysis of fluid film lubrication in artificial hip joint replacements with surfaces of high elastic modulus	247–256
Feneley, R. C. L.	A modified semi-automated technique for *in vitro* assessment of encrustation of materials	475–478
Fisher, J.	The wear of ultra-high molecular weight polyethylene sliding on metallic and ceramic counterfaces representative of current femoral surfaces in joint replacement	17–24
Fisher, J.	Analysis of fluid film lubrication in artificial hip joint replacements with surfaces of high elastic modulus	247–256
Fisher, J.	Wear of ultra-high molecular weight polyethylene acetabular cups in a physiological hip joint simulator in the anatomical position using bovine serum as a lubricant	265–269

© IMechE 1997

Fisher, J.	Friction of composite cushion bearings for total knee joint replacements under adverse lubrication conditions	451–465
Fleming, H. E.	Quality framework for force plate testing	213–219
Frank, T. G.	Technological aspects of minimal access surgery	129–144
Freeman, M. A. R.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Gepi-Attee, S.	A modified semi-automated technique for *in vitro* assessment of encrustation of materials	475–478
Gilbert, J. A.	Evaluation of the frictional properties of an elastomer with enhanced lipid-adsorbing ability	359–368
Goel, V. K.	Bone registration method for robot assisted surgery: pedicle screw insertion	221–233
Good, V.	Charnley wear model for validation of hip simulators—ball diameter versus polytetrafluoroethylene and polyethylene wear	25–36
Gossé, F.	A new oscillating saw for robotic aided surgery	301–308
Griffiths, J. G.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Grimshaw, P. N.	Quantitative assessment of anterior cruciate ligament deficiency: applied load versus applied displacement	441–449
Gustafson, A.	Charnley wear model for validation of hip simulators—ball diameter versus polytetrafluoroethylene and polyethylene wear	25–36
Hall, M. G.	Quality framework for force plate testing	213–219
Hanna, G. B.	Technological aspects of minimal access surgery	129–144
Hardaker, C. S.	Wear of ultra-high molecular weight polyethylene acetabular cups in a physiological hip joint simulator in the anatomical position using bovine serum as a lubricant	265–269
Harris, S. J.	Active compliance in robotic surgery—the use of force control as a dynamic constraint	285–292
Harris, S. J.	The Probot—an active robot for prostate resection	317–325
Harrison, A. J.	Simulation of resistance forces acting on surgical needles	335–347
Hassfeld, S.	Intraoperative guidance in maxillofacial and craniofacial surgery	277–283
Hauser, R.	A non-invasive patient registration and reference system for interactive intraoperative localization in intranasal sinus surgery	327–334
Haynes, D. R.	The role of polyethylene wear in joint replacement failure	65–72
Haynes, R. C.	Comparative dynamic evaluation of the sliding characteristics of the Gamma nail: a biomechanical analysis	411–417
Hibberd, R. D.	Active compliance in robotic surgery—the use of force control as a dynamic constraint	285–292
Hibberd, R. D.	The Probot—an active robot for prostate resection	317–325
Howie, D. W.	The role of polyethylene wear in joint replacement failure	65–72
Hukins, D. W. L.	An automated method for assessing routine radiographs of patients with total hip replacements	145–154
Hvid, I.	Simultaneous measurement of stiffness and energy absorptive properties of articular cartilage and subchondral trabecular bone	257–264
Imran, A.	Theoretical estimates of cruciate ligament forces: effects of tibial surfaces geometry and ligament orientations	425–439
Inooka, H.	On an ambulance stretcher suspension concerned with the reduction of patient's blood pressure variation	199–208
Ino-oka, E.	On an ambulance stretcher suspension concerned with the reduction of patient's blood pressure variation	199–208
Ishihara, K.	Evaluation of the frictional properties of an elastomer with enhanced lipid-adsorbing ability	359–368
Iwasaki, Y.	Evaluation of the frictional properties of an elastomer with enhanced lipid-adsorbing ability	359–368
Jin, Z. M.	Analysis of fluid film lubrication in artificial hip joint replacements with surfaces of high elastic modulus	247–256
Jin, Z. M.	Friction of composite cushion bearings for total knee joint replacements under adverse lubrication conditions	451–465
Johnson, G. R.	Computer simulation of the dynamics of a human arm and orthosis linkage mechanism	349–357
Kadoya, Y.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Karpinski, M. R. K.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Kaymak, Ö.	Biomechanics of the Gazi type pelvis external skeletal fixator	401–409
Kirtley, C.	Calculation of multi-segment rigid body dynamics using MATLAB	483–487
Knauth, M.	Intraoperative guidance in maxillofacial and craniofacial surgery	277–283
Kobayashi, A.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Kobayashi, A.	Biological reaction to debris in relation to joint prostheses	187–197
Kolar, M.	Development of a six station knee wear simulator and preliminary wear results	37–47
Korkusuz, F.	Biomechanics of the Gazi type pelvis external skeletal fixator	401–409

© IMechE 1997

Kotcheff, A. C. W.	An automated method for assessing routine radiographs of patients with total hip replacements	145–154
Kowalski, D.	Bone registration method for robot assisted surgery: pedicle screw insertion	221–233
Krygier, J. J.	Kinematics of the MATCO® hip simulator and issues related to wear testing of metal–metal implants	89–99
Kundu, B.	The Probot—an active robot for prostate resection	317–325
LaBerge, M.	Evaluation of the frictional properties of an elastomer with enhanced lipid-adsorbing ability	359–368
Lacroix, D.	Stress analysis of glenoid component design for shoulder arthroplasty	467–474
Lancaster, J. G.	The wear of ultra-high molecular weight polyethylene sliding on metallic and ceramic counterfaces representative of current femoral surfaces in joint replacement	17–24
Learmonth, I. D.	Factors contributing to the wear of polyethylene in clinical practice	49–57
Learmonth, I. D.	The pathogenesis of osteolysis in two different cementless hip replacements	59–63
Lee, V. S. P.	Stump–socket interface pressure as an aid to socket design in prostheses for trans-femoral amputees—a preliminary study	167–180
Lin, W. J.	Active compliance in robotic surgery—the use of force control as a dynamic constraint	285–292
Linde, F.	Simultaneous measurement of stiffness and energy absorptive properties of articular cartilage and subchondral trabecular bone	257–264
Lippincott, A.	Kinematics of the MATCO® hip simulator and issues related to wear testing of metal–metal implants	89–99
Lu, Z.	Frictional heating of bearing materials tested in a hip joint wear simulator	101–108
Lutze, T.	Intraoperative guidance in maxillofacial and craniofacial surgery	277–283
McGee, M. A.	The role of polyethylene wear in joint replacement failure	65–72
McGloughlin, T. M.	Contact stress analysis of the tibial component of prosthetic knee implants	391–399
McGowan, D. P.	Bone registration method for robot assisted surgery: pedicle screw insertion	221–233
McKellop, H.	Frictional heating of bearing materials tested in a hip joint wear simulator	101–108
Medley, J. B.	Kinematics of the MATCO® hip simulator and issues related to wear testing of metal–metal implants	89–99
Mei, Q.	The Probot—an active robot for prostate resection	317–325
Middleton, R.	Active compliance in robotic surgery—the use of force control as a dynamic constraint	285–292
Miles, A. W.	The influence of the stem–cement interface in total hip replacement—a comparison of experimental and finite element approaches	181–186
Miles, A. W.	Comparative dynamic evaluation of the sliding characteristics of the Gamma nail: a biomechanical analysis	411–417
Moctezuma, J. L.	A new oscillating saw for robotic aided surgery	301–308
Mohsen, A. M. M. A.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Monaghan, J. M.	Contact stress analysis of the tibial component of prosthetic knee implants	391–399
Muehling, J.	Intraoperative guidance in maxillofacial and craniofacial surgery	277–283
Nakabayashi, N.	Evaluation of the frictional properties of an elastomer with enhanced lipid adsorbing ability	359–368
Nathan, M. S.	The Probot—an active robot for prostate resection	317–325
Neale, S. D.	The role of polyethylene wear in joint replacement failure	65–72
O'Connor, J. J.	Parameter sensitivity of a mathematical model of the anterior cruciate ligament	235–246
O'Connor, J. J.	Theoretical estimates of cruciate ligament forces: effects of tibial surfaces geometry and ligament orientations	425–439
Odgaard, A.	Simultaneous measurement of stiffness and energy absorptive properties of articular cartilage and subchondral trabecular bone	257–264
Ozanian, T. O.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Parker, T. J.	Simulation of resistance forces acting on surgical needles	335–347
Paul, J. P.	Development of standards for orthopaedic implants	119–126
Paul, J. P.	Quality framework for force plate testing	213–219
Pearcy, M. J.	The role of polyethylene wear in joint replacement failure	65–72
Phillips, R.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Porter, M. L.	An automated method for assessing routine radiographs of patients with total hip replacements	145–154
Powell, G. L.	Evaluation of the frictional properties of an elastomer with enhanced lipid-adsorbing ability	359–368
Prendergast, P. J.	A model for fatigue crack propagation and remodelling in compact bone	369–375
Prendergast, P. J.	Stress analysis of glenoid component design for shoulder arthroplasty	467–474
Probst, R.	A non-invasive patient registration and reference system for interactive intraoperative localization in intranasal sinus surgery	327–334
Ratanapinunchai, J.	Calculation of multi-segment rigid body dynamics using MATLAB	483–487
Redhead, A. L.	An automated method for assessing routine radiographs of patients with total hip replacements	145–154

© IMechE 1997

Revell, P. A.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Revell, P. A.	Biological reaction to debris in relation to joint prostheses	187–197
Røhl, L.	Simultaneous measurement of stiffness and energy absorptive properties of articular cartilage and subchondral trabecular bone	257–264
Sagawa, K.	On an ambulance stretcher suspension concerned with the reduction of patient's blood pressure variation	199–208
Schulz, H.-J.	Intraoperative guidance in maxillofacial and craniofacial surgery	277–283
Schulz, H.-J.	A new oscillating saw for robotic aided surgery	301–308
Schuster, D.	A new oscillating saw for robotic aided surgery	301–308
Scott, G.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Seedhom, B. B.	A technique for measuring the compressive modulus of articular cartilage under physiological loading rates with preliminary results	155–165
Semlitsch, M.	Clinical wear behaviour of ultra-high molecular weight polyethylene cups paired with metal and ceramic ball heads in comparison to metal-on-metal pairings of hip joint replacements	73–88
Shepherd, D. E. T.	A technique for measuring the compressive modulus of articular cartilage under physiological loading rates with preliminary results	155–165
Sherman, K. P.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Smith, E. J.	The pathogenesis of osteolysis in two different cementless hip replacements	59–63
Smith, S. B.	Bone registration method for robot assisted surgery: pedicle screw insertion	221–233
Solomonidis, S. E.	Stump–socket interface pressure as an aid to socket design in prostheses for trans-femoral amputees—a preliminary study	167–180
Spence, W. D.	Stump–socket interface pressure as an aid to socket design in prostheses for trans-femoral amputees—a preliminary study	167–180
Stachowiak, G. W.	Application of numerical descriptors to the characterization of wear particles obtained from joint replacements	1–10
Stachowiak, G. B.	Application of numerical descriptors to the characterization of wear particles obtained from joint replacements	1–10
Stewart, T.	Friction of composite cushion bearings for total knee joint replacements under adverse lubrication conditions	451–465
Stone, R. S. W.	A technique for measuring contact force distribution in minimally invasive surgical procedures	309–316
Takahashi, T.	On an ambulance stretcher suspension concerned with the reduction of patient's blood pressure variation	199–208
Tanzer, M.	Kinematics of the MATCO® hip simulator and issues related to wear testing of metal–metal implants	89–99
Taylor, C. J.	An automated method for assessing routine radiographs of patients with total hip replacements	145–154
Taylor, D.	A model for fatigue crack propagation and remodelling in compact bone	369–375
Thomas, T. A.	Simulation of resistance forces acting on surgical needles	335–347
Thomson, K. D.	Estimation of loads and stresses in abdominal muscles during slow lifts	271–274
Toutoungi, D. E.	Parameter sensitivity of a mathematical model of the anterior cruciate ligament	235–246
Unsworth, A.	Development of a six station knee wear simulator and preliminary wear results	37–47
Unsworth, A.	Further studies into proximal interphalangeal joint dimensions for the design of a surface replacement prosthesis: medullary cavities and transverse plane shapes	377–390
Viant, W. J.	A computer assisted orthopaedic surgical system for distal locking of intramedullary nails	293–300
Wang, H.	Rolling resistance of articular cartilage due to interstitial fluid flow	419–424
Waugh, H. V.	A prototype model for renal vasculature and its application in haemodialyser miniaturization	479–482
Westermann, B.	A non-invasive patient registration and reference system for interactive intraoperative localization in intranasal sinus surgery	327–334
Wheeler, J. P. G.	The influence of the stem–cement interface in total hip replacement—a comparison of experimental and finite element approaches	181–186
Wickham, J. E. A.	The Probot—an active robot for prostate resection	317–325
Willert, H. G.	Clinical wear behaviour of ultra-high molecular weight polyethylene cups paired with metal and ceramic ball heads in comparison to metal-on-metal pairings of hip joint replacements	73–88
Williams III, P. F.	Evaluation of the frictional properties of an elastomer with enhanced lipid-adsorbing ability	359-368
Wirtz, C. R.	Intraoperative guidance in maxillofacial and craniofacial surgery	277–283
Wroblewski, B. M.	Wear of the high-density polyethylene socket in total hip arthroplasty and its role in endosteal cavitation	109–118
Yamac, T.	The size and shape of particulate polyethylene wear debris in total joint replacements	11–15
Zavatsky, A. B.	Parameter sensitivity of a mathematical model of the anterior cruciate ligament	235–246

© IMechE 1997